



CERTOMAT[®] MO II
For economic benchtop
shaking

CERTOMAT® MO II

For economic benchtop shaking

The CERTOMAT® MO II from Sartorius has proven its value in many laboratories worldwide. Due to its small footprint and user-friendly design it is an ideal shaker for every application. In microbiology laboratories the CERTOMAT® MO II is used for cultivation of cells at room temperature. In chemistry it allows to mix various liquids or extract substances using phase separation methods.

For applications requiring temperature control, the CERTOMAT® MO II can be combined with the incubation hoods CERTOMAT® H or HK. This way bacteria or yeast cells can be grown at defined temperatures above or below ambient temperature.

Erlenmeyer flasks, reagent tubes, various bottles or even microtiter plates are fixed on the shaker using clamps, racks or the universal mounting system. Alternatively, Sticky tape can be used to hold light items in place during agitation.

For applications requiring higher load capacities the use of our models CERTOMAT® S II or CERTOMAT® RM is recommended. If your application calls for temperature-controlled shaking our incubation shakers CERTOMAT® IS or CERTOMAT® BS-1 are good options.

Benefits

Small footprint

Sturdy construction

Analog speed and time control

Shaking speed 40–350 rpm

Choice of 12.5 or 25 mm orbit

Voltage selector 230 V/115 V, 50–60 Hz

Can be combined with incubation hoods CERTOMAT® H | HK

Compatible with complete range of CERTOMAT® accessories




Accessories



Reference	Description
	Tray type E (420×420 mm) equipped with stainless steel clamps for Erlenmeyer flasks
BBI-885 3533	39 clamps for flasks 100 ml
BBI-885 3568	20 clamps for flasks 250 ml
BBI-885 3584	14 clamps for flasks 500 ml
BBI-885 3606	9 clamps for flasks 1,000 ml
	Tray type E (420×420 mm) equipped with plastic clamps for Erlenmeyer flasks
BBI-885 3688	39 clamps for flasks 100 ml
BBI-885 3666	19 clamps for flasks 250 ml
BBI-885 3677	14 clamps for flasks 500 ml
	Universal tray, to be completed with clamps, racks or mounting system Type EU (420×420 mm)
BBI-885 3002	
	Stainless steel clamps for tray type EU
BBI-885 4505	for Erlenmeyer flasks 25 ml (max. 49)
BBI-885 4513	for Erlenmeyer flasks 50 ml (max. 48)
BBI-885 4521	for Erlenmeyer flasks 100 ml (max. 24)
BBI-885 4556	for Erlenmeyer flasks 250 ml (max. 17)
BBI-885 4572	for Erlenmeyer flasks 500 ml (max. 12)
BBI-885 4599	for Erlenmeyer flasks 1,000 ml (max. 8)
BBI-885 4610	for Erlenmeyer flasks 2,000 ml (max. 4)
BBI-885 4629	for Erlenmeyer flasks 3,000 ml (max. 4)
BBI-885 4564	for Fernbach flasks 450 ml (max. 8)
BBI-885 4600	for Fernbach flasks 1,800 ml (max. 4)
BBI-885 4640	for Fernbach flasks 2,800 ml (max. 4)
	Plastic clamps reinforced with glass fibre
BBI-885 4700	for Erlenmeyer flasks 100 ml (max. 24)
BBI-885 4711	for Erlenmeyer flasks 250 ml (max. 17)
BBI-885 4722	for Erlenmeyer flasks 500 ml (max. 12)
BBI-885 4733	for Erlenmeyer flasks 1,000 ml (max. 8)
	Hinged racks for test tubes (4 racks max. on tray EU)
BBI-885 3134	for 64 tubes Ø 14 mm
BBI-885 3142	for 42 tubes Ø 16 mm
BBI-885 3150	for 36 tubes Ø 18 mm
BBI-885 3169	for 33 tubes Ø 20 mm
BBI-885 3185	for 18 tubes Ø 25 mm
BBI-885 3177	for 16 tubes Ø 30 mm
	Hinged racks for centrifugation tubes (4 racks max. on tray EU)
BBI-885 3088	for 42 tubes Ø 16 mm
BBI-885 3096	for 36 tubes Ø 18 mm
BBI-885 3193	for 33 tubes Ø 20 mm
BBI-885 3240	for 16 tubes Ø 30 mm




Reference	Description
BBI-886 4497	Sticky tape for universal trays Standard, Width 30 mm, roll of 50 m
BBI-886 0419	Premium, Width 30 mm, roll of 10 m, for repeated use
BBI-886 4470	Anti-skid layer (not shown) 380×450 mm, for individual cut



BBI-885 0321	Holders for microtiter plates, stainless steel for 1 standard 96-well plate or deepwell plate standard plates: max. 12 holders on EU tray deepwell plates: max. 9 holders on EU tray
--------------	--



BBI-885 4238	Universal mounting system Basic element B-2 for tray EU
BBI-885 4254	Universal clamping rod for basic elements B-2



BBI-886 1005	Shaking flasks, DURAN, Erlenmeyer type, 3 baffles at 120°, straight rim Erlenmeyer flasks 300 ml, pack of 10
BBI-886 1013	Erlenmeyer flasks 500 ml, pack of 10
BBI-886 1021	Erlenmeyer flasks 1,000 ml, pack of 10
BBI-886 1022	Erlenmeyer flasks 2,000 ml, pack of 10



BBI-886 1064	Shaking flasks, DURAN, Erlenmeyer type, 3 baffles at 120°, straight rim, connector GL 14 Erlenmeyer flasks 300 ml, pack of 10
BBI-886 1072	Erlenmeyer flasks 500 ml, pack of 10
BBI-886 1080	Erlenmeyer flasks 1,000 ml, pack of 10



BBI-886 1099	Caps for Erlenmeyer flasks, straight rim Cap Aluminium, pack of 10
BBI-886 1102	Cap Stainless steel, pack of 10



BBI-886 0998	Shaking flasks, DURAN, Erlenmeyer type, 3 baffles at 120°, narrow neck for plug Erlenmeyer flasks 500 ml, pack of 10
--------------	--

Ordering information and technical specifications

Ordering information

CERTOMAT® MO II version with 12.5 mm orbit 115/230 V/50–60 Hz	BBI-886 0858	CERTOMAT® MO II/12.5 mm
CERTOMAT® MO II version with 25 mm orbit 115/230 V/50–60 Hz	BBI-886 0866	CERTOMAT® MO II/25 mm

Technical specifications

Mechanical Data	Dimensions Weight (without tray) Housing Drive mechanism Trays, type size Tray fixation Max. load Protection	W x H x D = 430 x 123 x 400 mm 31 kg Steel construction Brushless motor, triple eccentric drive Type E EU (420 x 420 mm) By screws 10 kg IP21
Electrical data	Connection Protection class Line voltage Amperage Fuses Interference	Class I cold socket, separate cable approx. 3 m I 230 V 50 Hz or 115 V 60 Hz, adjustable 0.8 A at 230 V, 1.6 A at 115 V 2 x T1.0 A at 230 V, 2 x T2.0 A at 115 V class N according to EN 55014-2
Operating data	Mode of shaking Shaking speed Accuracy Setting of speed Timing Ambient temperature Humidity	Orbital, Ø 12,5 mm or 25 mm, according to version 40 to 350 rpm max. ±5% of final value By potentiometer 0 to 120 minutes and continuous, mechanical timer +10 °C to + 60 °C Avoid extreme humidity

All instruments are delivered without tray and other accessories.

For growing cells or mixing liquids, a tray is needed together with additional accessories to hold shaking flasks, separation funnels or tubes.

Sales and Service Contacts

For further contacts, visit www.sartorius.com

Europe

Germany

Sartorius AG
Weender Landstrasse 94-108
37075 Goettingen

Phone +49.551.308.0
Fax +49.551.308.3289

www.sartorius.com

Sartorius BBI Systems GmbH
Schwarzenberger Weg 73-79
34212 Melsungen

Phone +49.5661.71.3400
Fax +49.5661.71.3702

www.sartorius.com

Austria

Sartorius Ges.m.b.H. Wien
Franzosengraben 12
A-1030 Vienna

Phone +43.1.7965763.18
Fax +43.1.796576344

Belgium

Sartorius Technologies N.V.
Luchthavenlaan 1-3
1800 Vilvoorde

Phone +32.2.756.0670
Fax +32.2.756.0681

Denmark

Sartorius A/S
Himmelev Bygade 49
4000 Roskilde

Phone +45.70.23.4400
Fax +45.46.30.4030

France

Sartorius S.A.S.
4, rue Emile Baudot
91127 Palaiseau Cedex

Phone +33.1.6919.2100
Fax +33.1.6920.0922

Italy

Sartorius S.p.A.
Via dell'Antella, 76/A
50011 Antella-Bagno a Ripoli (FI)

Phone +39.055.63.40.41
Fax +39.055.63.40.526

Netherlands

Sartorius Filtratatie B.V.
Edisonbaan 24
3439 MN Nieuwegein

Phone +31.30.6025080
Fax +31.30.6025099

Spain

Sartorius, S.A.
C/Isabel Colbrand 10 -12,
Planta 4, Oficina 121
Poligono Industrial de Fuencarral
28050 Madrid

Phone +34.91.3586102
Fax +34.91.3588804

Switzerland

Sartorius Schweiz AG
Lerzenstrasse 21
8953 Dietikon

Phone +41.1.746.50.00
Fax +41.1.746.50.50

U.K.

Sartorius Ltd.
Longmead Business Park
Blenheim Road, Epsom
Surrey KT19 9 QQ

Phone +44.1372.737100
Fax +44.1372.720799

America

USA

Sartorius North America, Inc.
131 Heartland Blvd.
Edgewood, New York 11717

Phone +1.631.254.4249
Toll-Free +1.800.3687178
Fax +1.631.254.4253

Sartorius BBI Systems, Inc.
2800 Baglyos Circle
Bethlehem, PA 18020

Phone +1.610.866.4800
Fax +1.610.866.4890

Argentina

Sartorius Argentina S.A.
Calle Avalos 4251 (B1605ECS) Munro
Buenos Aires

Phone +54.11.4721.0506
Fax +54.11.4762.2333

Brazil

Sartorius do Brasil Ltda.
Rua Santo André, 331
09020-230 Santo André
São Paulo

Phone +55.11.4438.3833
Fax +55.11.4438.2355

Mexico

Sartorius de México S.A. de C.V.
Circuito Arquitectos No. 11
Despacho 201
Ciudad Satélite
53100 Naucalpan, Estado de Mexico

Phone +52.55.62.1102
Fax +52.55.62.2942

Asia | Pacific

China

Beijing Sartorius Instrument & System
Engineering Co., Ltd.

- Beijing Rep. Office -
Dong Hu Qu, Wang Jing
Industrial Zone
Chao Yang District
100102 Beijing, P.R.C.
P.O. Box 8516

Phone +86.10.6439.2552
Fax +86.10.6439.2726

Sartorius Ltd.
Unit 1110-12, Lu Plaza,
2 Wing Yip Street
Kwun Tong, Kowloon, Hong Kong

Phone +852.2774.2678
Fax +852.2766.3526

India

Sartorius India Private Ltd.
10, 6th Main, 3rd Phase Peenya
KIADB Industrial Area
Bangalore - 560 058

Phone +91.80.2839.1963 | 0461
Fax +91.80.2839.8262

Japan

Sartorius K.K.
KY Building, 8-11
Kita Shinagawa 1-chome
Shinagawa-ku
Tokyo 140-0001

Phone +81.3.3740.5407
Fax +81.3.3740.5406

South Korea

Sartorius Korea Biotech
B-1023, Paragon
17-2, Jungja-Dong, Bundang-Gu
Sungnam, Gyunggi-Do
463-811, South Korea

Phone +82.31.782.7011
Fax +82.31.782.7666

Malaysia

Sartorius (Malaysia) Sdn. Bhd.
Lot L3-E-3B, Enterprise 4
Technology Park Malaysia
Bukit Jalil
57000 Kuala Lumpur

Phone +60.3.8996.0622
Fax +60.3.8996.0755

Singapore

Sartorius Singapore Pte. Ltd.
10, Science Park Road, The Alpha
#02-25, Singapore Science Park 2
Singapore 117684

Phone +65.6872.3966
Fax +65.6778.2494

Australia

Sartorius Australia Pty. Ltd.
Unit 17/104 Ferntree Gully Road
Waverley Business Park
East Oakleigh, Victoria 3166

Phone +61.3.9590.8800
Fax +61.3.9590.8828